

# Durafalt® HD/HD+

## Technical data sheet

**Durafalt® HD/HD+ is a unique stone mastic asphalt (SMA) surfacing solution designed for very heavy, slow moving traffic. It contains a polymer modified binder (PMB) with an exceptionally high softening point.**

**Durafalt HD** is a strong and durable surface course (non-clause 942) designed to withstand heavy load traffic.

**Durafalt HD+** is a combined solution (non-clause 942) that contains fuel resisting properties and is designed to withstand heavy load traffic. Available in 10mm and 14mm nominal sizes.

### Benefits

- Cost-effective
- Texture depth range 1.1mm – 1.8mm
- Durable
- High deformation resistance
- Good noise reduction
- Reduced spray
- Fuel resisting properties
- Good workability
- Enhanced ride quality
- Excellent load spreading ability from very heavy slow moving traffic at higher temperatures to prevent wheel track deformation

**Please note:** 7 days' notice required to stock specialist binder.

**Also available with the following options:**

**era®/CleanAir®/RAP**

### Use this product for

- Carriageways
- Major paved areas
- Industrial



RESISTANCE TO  
DEFORMATION



NOISE  
REDUCTION



SPRAY  
REDUCTION



FUEL RESISTING  
PROPERTIES



ENHANCED  
DURABILITY



REDUCED  
CO<sub>2</sub>

Please see asphalt product matrix for further information or contact technical:

[northasphaltsales@uk.heidelbergmaterials.com](mailto:northasphaltsales@uk.heidelbergmaterials.com)

[southwestasphaltsales@uk.heidelbergmaterials.com](mailto:southwestasphaltsales@uk.heidelbergmaterials.com)

[southwalesasphaltsales@uk.heidelbergmaterials.com](mailto:southwalesasphaltsales@uk.heidelbergmaterials.com)

[southeastasphaltsales@uk.heidelbergmaterials.com](mailto:southeastasphaltsales@uk.heidelbergmaterials.com)