

Heidelberg Materials PowerSand CBS Extra

Technical data sheet

Heidelberg Materials PowerSand CBS Extra is a low carbon, non-traditional stabilised backfill as defined in ENA TS 97-1.

It is obtained from approved selected sources and chosen on the basis of density and cohesion characteristics to provide a maximum dry state thermal resistivity of 0.75km/W.

It is used in the installation of underground electricity cables due to its low thermal resistance.

Benefits

- Keeps cables cool due to low thermal resistance
- Consistent for ease of use and ultimate performance
- National availability
- UKAS test certificates available if requested
- Meets or exceeds the requirements of ENA TS 97-1

Properties	Clause	ENA TS 97-1 requirement	Compliance status
Particle size distribution	7.2.1	Minimum 95% passing a 5mm sieve	Pass
Dry relative density	7.3.3.2	Minimum of 1.6mg/m ³	Pass
Cohesion	N/A	Test to Annex C (P or F)	Pass
Thermal resistivity	7.3.3.1	Maximum 0.75km/W	Pass

For guidance on application and installation we recommend that the contractor follows the process outlined in 'Document ECS 02-0019 Installation of Underground Cables 0 LV to 132KV'.

Further information

Contact enquiries@uk.heidelbergmaterials.com

Further copies of this technical data sheet may be obtained from Heidelberg Materials UK