

Postfix

Product guide

Heidelberg Materials Postfix is a simple to use fast-setting concrete mix for fixing posts in the ground. It requires no premixing before use. Heidelberg Materials Postfix contains Portland Cement and special additives together with sharp sand and 10mm gravel. Heidelberg Materials Postfix is used for fence posts, gate posts, pergolas, garden lighting and rotary lines.

Conditions of use

- As a general rule, concrete should be placed within the range of 5°C to 30°C.
- In cold weather, setting times may be extended and strength development delayed.
- Freshly placed Postfix should be protected from low temperatures to avoid frost damage.
- Heidelberg Materials Cement cannot be held responsible for poor workmanship.
- To avoid premature deterioration of Heidelberg Materials Postfix cement, please follow the correct storage requirements.

Instructions for use

01. Position post in hole.
02. Add two litres of water.
03. Empty the complete bag into hole around the post.
04. Check the position of the post and adjust as necessary.
05. Tamp to remove any air bubbles.
06. If necessary, sprinkle more water to mix any remaining powder left on the surface. Allow 5-10 minutes for initial set to take place – following this, the post will remain in a vertical position unsupported. Postfix will achieve appreciable strength after 4 hours depending on ambient conditions but is best left overnight before attaching fence panels etc.

